



Revision 20211206

HAPSOFT™ S3620

PP SHORT GLASS FIBER REINFORCED

DESCRIPTION

HAPSOFT^{IM} PPcompound (PPc) S3620 is a 20% short glass fiber reinforced polypropylene copolymer compound for injection moulding applications. The compound is UV stabilized and the glass fibers are chemically coupled to the PP matrix. This compound combines a matt surface, good sound dampening and excellent scratch resistance with soft-touch haptics and is especially designed to ensure the aesthetic quality of visible and touchable automotive interior applications. The grade is currently available in black and natural. All other colors are on request.

HAPSOFTTM PPc S3620 is a designated automotive grade. IMDS ID: 679564115

TYPICAL PROPERTY VALUES

PROPERTIES TYPICAL VALUES UNITS TEST METHODS POLYMER PROPERTIES Melt Flow Rate (MFR) ISO 1133 at 230 °C and 2.16 kg 8 dg/min Density⁽¹⁾ 1040 kg/m³ ISO 1183 Filler content 20 SABIC method % Mould shrinkage (2) 24 hours after injection moulding 0.4 % SABIC method MECHANICAL PROPERTIES (1) Tensile 2600 MPa ISO 527/1A Tensile modulus stress at break 35 MPa ISO 527/1A 7 ISO 527/1A strain at break % Flexural test Flexural modulus 2500 MPa ISO 178/1A Izod impact notched (3) at 23 °C 40 kJ/m² ISO 180/1A THERMAL PROPERTIES (1) Heat deflection temperature °C at 1.80 MPa (HDT/A) 100 ISO 75 Coeff. of linear thermal expansion -30 °C to 100 °C 50 ISO 11359-2 µm/mK

(1) Injection molded sample ISO527-1A

(2) Injection molded plaque 65x65x3.2mm

(3) N.B.: No Break

STORAGE AND HANDLING

Avoid prolonged storage in open sunlight, high temperatures (<50 °C) and/or high humidity as this could well speed up alteration and consequently loss of quality of the material and/or its packaging. Keep material completely dry for good processing.





DISCLAIMER

Any sale by SABIC, its subsidiaries and affiliates (each a "seller"), is made exclusively under seller's standard conditions of sale (available upon request) unless agreed otherwise in writing and signed on behalf of the seller. While the information contained herein is given in good faith, SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND NONINFRINGEMENT OF INTELLECTUAL PROPERTY, NOR ASSUMES ANY LIABILITY, DIRECT OR INDIRECT, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OR PURPOSE OF THESE PRODUCTS IN ANY APPLICATION. Each customer must determine the suitability of seller materials for the customer's particular use through appropriate testing and analysis. No statement by seller concerning a possible use of any product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right.